



# SolarEdge Single Phase Inverters 16A



## The best choice for SolarEdge enabled systems

- Superior efficiency (97.6%)
- Small, lightweight and easy to install
- Built-in module-level monitoring
- Communication to internet via Ethernet or Wireless
- IP65 – Outdoor and indoor installation



SE3500-XXX\*

SE4000-16A

architects of energy™

# Single Phase Inverters - 16A

## SE3500-XXX\*/SE4000-16A

All our inverters are part of SolarEdge's innovative system designed to provide superior performance at a competitive price. The SolarEdge inverter combines a sophisticated, digital control technology and a one stage, ultra-efficient power conversion

architecture to achieve superior performance – over 97% efficiency and best-in-class reliability. Our fixed-voltage technology ensures the inverter is always working at its optimal input voltage, regardless of the number of modules or environmental conditions.

### TECHNICAL DATA

	SE3500-XXX*	SE4000-16A	
<b>OUTPUT</b>			
Rated AC Power Output	3500	4000	W
Maximum AC Power Output	3500	4000	W
AC Output Voltage (Nominal)	400/230 ; 380/220		Vac
AC Output Voltage Range	184 - 264.5		Vac
AC Frequency (Nominal)	50 / 60 ± 5		Hz
Maximum Continuous Output Current	16		A
Residual Current Detector / Residual Current Step Detector	300 / 30		mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes		
<b>INPUT</b>			
Recommended Maximum DC Power**(Module STC)	3900	4400	W
Transformer-less, Ungrounded	Yes		
Maximum Input Voltage	500		Vdc
Nominal DC Input Voltage	350		Vdc
Maximum Input Current	13.5	15.5	Adc
Reverse-Polarity Protection	Yes		
Ground-Fault Isolation Detection	600kΩ Sensitivity		
Maximum Inverter Efficiency	97.6		%
European Weighted Efficiency	97.5		%
Nighttime Power Consumption	< 2.5		W
<b>ADDITIONAL FEATURES</b>			
Supported Communication Interfaces	RS485, RS232, Ethernet, Zigbee (optional)		
<b>STANDARD COMPLIANCE</b>			
Safety	IEC-62103 (EN50178), IEC-62109		
Grid Connection Standards	VDE 0126-1-1, VDE-AR-N-4105, AS-4777, RD-1663 , DK 5940		
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B		
RoHS	Yes		
<b>INSTALLATION SPECIFICATIONS</b>			
AC Output	Cable Gland - diameter 11-17		mm
DC Input	MC4		
Dimensions (HxWxD)	540 x 315 x 172	540 x 315 x 191	mm
Weight	19	20.5	kg
Cooling	Natural Convection		
Operating Temperature Range	-20 - +50		°C
Protection Rating	IP65 - Outdoor and Indoor		
Bracket Mounted (Bracket Provided)			

\* XXX can be GBR (United Kingdom), DEN (Denmark), PRT (Portugal), POL (Poland); for other countries contact SolarEdge

\*\* Higher input DC power may be installed; analyze yearly AC performance.



■ USA ■ Germany ■ Italy ■ France ■ Japan ■ China ■ Israel

[www.solaredge.com](http://www.solaredge.com)

**solar**edge  
architects of energy™

© SolarEdge Technologies, Inc. 2009-2012. All rights reserved. SOLAREEDGE, the SolarEdge logo, ARCHITECTS OF ENERGY and OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners.. Date: 06/2012. V.01. Subject to change without notice.